

### Product Shelf Life Recommendation

Fresh-Lock® Slider Track is extruded plastic and, therefore, has no expiration date after being converted into a pouch. For best performance, we recommend that Fresh-Lock® Slider Track be stored in optimal storage conditions and converted within 2 years from the date of manufacture, and as such, we warranty our product up to this limit.

### Optimal Storage Conditions:


Temperature: 0 to 120° F (-18 to 49° C)

Relative Humidity: 10 to 75%

### Roll Handling Procedure

All rolls of slider track will be individually wrapped and loaded onto a pallet in the orientation depicted on the right to prevent entanglement. At no time should rolls be placed on end.

- ✓ Upon receipt of pallet by the customer, inspect for damage.
- ✓ Report any damage to your customer service representative.
- ✓ Store in original package, preferably on pallet until ready to use.
- ✓ Pallets can only be double stacked if product is still in its original shipping packaging.
- ✓ Never drop a spool onto its side as it can change the orientation of the product.
- ✓ When ready to use, remove spool from bag, maintaining orientation. Use a core hoist to transport to the machine.



**H-Orientation**  
Correct shipping and storage orientation



**I-Orientation**  
Avoid standing rolls on end

- ✓ Install track on unwind shaft.
- ✓ Remove stretch wrap by hand from spool at a 90° angle.
- ✓ Do not use razor to cut stretch wrap.